

USER INSTRUCTION

NICKELOR 500				
Colour : Grey/Gun metal	Use : Bath	Colour coordinates : L:74.0	a: 2.0	b: 3.0

Product description

NICKELOR 500 is a fluoride-based acid nickel plating process, which deposits a black nickel-tin alloy (gunmetal-anthracite). It is generally used as an economical finish to give objects a black colour with a durable, compact and even deposit. Its ease of control and electrolytic stability make it possible to achieve deposits with a consistent quality with both frame and barrel processes .

Condizioni operative

Parameter	Valore medio suggerito	
Deposition time	180 seconds	
Temperature	50 °C	
Voltage	1.5 V	
Current density	0.7 A/dm ²	
Cathodic efficiency	0.7 mg/Amin	
Deposition speed	0.3 μm/min	
Anodes	Graphite	
Agitation	Moderate	
Ventilation	Necessary	

Maintenance of plating bath

For small plating solution volumes (up to 10 litres) we suggest to use the bath without replenisher. For higher volumes we suggest to use the related replenisher composing the bath:

- NICKELOR 540RA : add 0.8 g every 100 Amin.
- NICKELOR 540RB : add 0.8 g every100 Amin.
- NICKELOR 500RN : add after analysis.
- NICKELOR 543 : add after analysis.

Safety Information

Please refer to the safety data sheets for any information regarding safety and disposal (MSDS).



USER INSTRUCTION

NICKELOR 500				
Colour : Grey/Gun metal	Use : Bath	Colour coordinates : L : 74.0	a: 2.0	b: 3.0

Notes

Instructions indicated in Our Process technical data sheets are the result of attentive checks and have been written as a guideline. They represent the best of our knowledge and refer to a normal use of our products. Such products are guaranteed in their quality up to the delivery: we cannot guarantee for the correct use of them, as this action in not under our direct control (addiction or correction to plating baths are made by customer's personnel). As a consequence, process instructions have not to be intended as a guarantee of the final result in the use of our products.

Related products

Cod.Articles	Description	Colour	Packaging
NI040901	NICKELOR 500 Make up solution	Grey	25 L
NI040610	NICKELOR 540RA Tin replenisher		10 kg
NI040710	NICKELOR 540RB Conducting salts		10 Kg
NI040710	NICKELOR 500RN Nickel replenisher		10 L
NI040825	NICKELOR 543 blackening agent		10 L