

USER INSTRUCTIONS

STR-T27SP

LACQUERS STRIPPER

Colour : — Use : Bath Colour coordinates : L: — a: — b: —

Product description

STR-T27SP is a specific stripper for acrylic and polyurethane lacquers.

Operating conditions

Parameter	Average suggested value	
Deposition time	300 seconds	
Temperature	25 °C	
Voltage	-	
Current density	-	
Cathodic efficiency	-	
Stripper speed	-	
Anodes	-	
Agitation	Moderate	
Ventilation	Necessary	

Maintenance of plating bath

The consumption of the solution is linked to the quantity of stripped lacquer. Usually the user understand clearly when is necessary to change the solution.

Safety Information

Please refer to the safety data sheets for any information regarding safety and disposal (MSDS).



USER INSTRUCTIONS

STR-T27SP

LACQUERS STRIPPER

Colour : — Use : Bath Colour coordinates : L: — a: — b: —

Preparation of the galvanic bath

STR-T27SP is supplied in concentrated version and must to be diluted with water before the use. In order to prepare 10 liters of ready to use solution follow the steps :

- 1. Switch on the ventilation system and all safety operation.
- 2. Fill up the tank with 9 liters of STR-T27SP
- 3. Add 1 liter of water in order to create a water film on the surface. This operation is just to avoid the strong evaporation of solvents present in the ST-T27SP solution.
- 4. Start with working operations putting inside the articles.

Notes

Instructions indicated in Our Process technical data sheets are the result of attentive checks and have been written as a guideline. They represent the best of our knowledge and refer to a normal use of our products. Such products are guaranteed in their quality up to the delivery: we cannot guarantee for the correct use of them, as this action in not under our direct control (addiction or correction to plating baths are made by customer's personnel). As a consequence, process instructions have not to be intended as a guarantee of the final result in the use of our products.

Products related

Cod.Articles	Description	Colour	Packaging
ST010625	STR-T27SP stripper for lacquer	-	5 - 25 Liters